

3M™ Novec™ 71DE Engineered Fluid

Introduction

3M™ Novec™ 71DE Engineered Fluid is a hydrofluoroether, Methyl Nonafluorobutyl Ether (C₄F₉OCH₃), in an azeotrope formulation with trans-1,2-dichloroethylene (t-DCE). This mixture is a true azeotrope, with constant vapor and liquid composition at its boiling point.

This fluid is ideal for medium-duty cleaning and degreasing tasks, as well as specialty solvent applications, and is intended to replace ozone-depleting materials in many applications. It has zero ozone depletion potential and other favorable environmental properties (see Table 2). Novec 71DE fluid has a time-weighted average exposure guideline of 750 ppm (eight hour average) for the 3M™ Novec™ 7100 Engineered Fluid component, and 200 ppm (eight hour average) for trans-1,2-dichloroethylene (t-DCE). These exposure guidelines suggest there is a large margin of safety for use of Novec 71DE fluid in its intended cleaning applications.

The increased solvency and low surface tension, nonflammability and constant composition during boiling of Novec 71DE fluid make it ideal for immersion and vapor degreasing applications. These properties also may make the azeotrope ideal for certain coating and lubricant deposition applications where increased solvency is required.

Applications

- Cleaning, rinsing and drying agent
 - Cleaning of oils, greases, waxes
- Specialty solvent applications, including coatings

For information on other applications, contact your 3M representative or 3M authorized distributor.

Material Description

Ingredients	3M™ Novec™ 71DE Engineered Fluid
Methyl Nonafluorobutyl Ether ¹	50% by weight
Trans-1,2-dichloroethylene	50% by weight
Appearance	Clear, colorless

¹Novec 7100 fluid (C₄F₉OCH₃) consists of two inseparable isomers with essentially identical properties. These are (CF₃)₂CFCH₂OCH₃ (CAS No. 163702-08-7) and CF₃CF₂CF₂CF₂OCH₃ (CAS No. 163702-07-6).

Typical Physical Properties

Table 1

Properties	3M™ Novec™ 71DE Engineered Fluid	CFC-113	HCFC-141b	HCFC-225 ca/cb	HFC-4310
Formulation	Azeotrope ¹	C ₂ Cl ₃ F ₃	CCl ₂ FCH ₃	C ₃ Cl ₂ HF ₅	Azeotrope ²
Boiling Point (°C)	41	48	32	54	39
Freeze Point (°C)	-24 ³	-35	-103	-131	NA
Liquid Density (g/ml)	1.37	1.56	1.23	1.55	1.41
Surface Tension (dynes/cm)	16.6	17.3	19.3	16.2	15.2
Kauri-Butanol Value	27	31	56	31	NA
Vapor Pressure (mmHg)	383	331	569	290	464
Viscosity (cps)	0.45	0.68	0.43	0.59	0.49
Heat of Vaporization (cal/g @ boiling point)	48	35	53.3	34.6	43.3

¹ 50% 3M™ Novec™ 7100 (C₄F₈OCH₃), 50% t-1,2-dichloroethylene

² 62% HFC-4310 (C₃H₂F₁₀), 38% trans-1,2-dichloroethylene

³ Critical Solution Temperature

Data compiled from published information.

Not for specification purposes. All values @ 25°C unless otherwise specified.

Environmental and Safety Properties

Table 2

Properties	3M™ Novec™ 71DE Engineered Fluid	CFC-113	HCFC-141b	HCFC-225 ca/cb	HFC-4310 ¹
Ozone Depletion Potential—ODP ²	0.00	0.80	0.10	0.03	0.00
Global Warming Potential ³	160	6000	700	180/620	1050
Flash Point	None	None	None	None	None

¹ 62% HFC-4310 (C₃H₂F₁₀), 38% trans-1,2-dichloroethylene

² CFC-11=1.0

³ GWP—100 year ITH, CO₂ = 1.0

Regulatory Status

The U.S. Environmental Protection Agency (EPA) has listed all components of 3M™ Novec™ 71DE Engineered Fluid as “acceptable,” without restrictions, under the EPA’s Significant New Alternatives Policy (SNAP) program.

Regulations on Chlorine-Containing Solvents

Table 3

Regulation	Trans-1,2-dichloroethylene	Trichloroethylene	Perchloroethylene	Methylene Chloride
VOC Designation	Yes	Yes	Yes	No
Reportable Quantity for Accidental Release	1000 lbs. (2000 lbs. in Novec 71DE)	100 lbs.	100 lbs.	1000 lbs.
Regulated if Emitted into Water	Yes	Yes	Yes	Yes
Hazardous Air Pollutant	No	Yes	Yes	Yes
Annual Reporting (EPCRA 313) (SARA)	No	Yes	Yes	Yes
OSHA List of toxins/carcinogens	No	Yes	Yes	Yes

Data compiled from published information.

Not for specification purposes.

Regulations and Reporting

Because of its favorable health and environmental properties, trans-1,2-dichloroethylene (t-DCE) is less regulated in the areas noted compared to the other chlorinated solvents in Table 3. Regulations affecting 3M™ Novec™ 71DE Engineered Fluid include VOC emissions of t-DCE and ethanol and reporting requirements if trans is emitted into water or if a spill of 2000 lbs. or more of Novec 71DE fluid occurs. t-DCE is not considered a Hazardous Air Pollutant (HAP) and is not subject to annual reporting requirements.

Environmental Policy

3M will continue to recognize and exercise its responsibility to prevent pollution at the source wherever and whenever possible; develop products that will have a minimal effect on the environment; conserve natural resources through the use of reclamation and other appropriate methods; assure that its facilities and products meet and sustain the regulations of all federal, state and local environmental agencies; assist, wherever possible, governmental agencies and other official organizations engaged in environmental activities.

Safety and Handling

Novec 71DE fluid is nonflammable and does not exhibit flammability characteristics under normal operating and storage conditions. This fluid is highly resistant to thermal breakdown and hydrolysis in storage and during use.

Before using this product, please read the current Material Safety Data Sheet available through your 3M sales or technical service representative and the precautionary statement on the product package. Follow all applicable precautions and directions.

Packaging and Availability

Novec 71DE fluid may be ordered in the following container sizes:

- 1-gallon pail
- 5-gallon drum
- 55-gallon drum

Recycle and Disposal Options

Used Fluid Return Program

3M offers a program for free pickup and return of used 3M specialty fluids in the U.S. A pre-negotiated handling agreement between users and our authorized service provider offers users broad protection against future liability for used 3M product. The fluid return program is covered by independent third-party financial and environmental audits of treatment, storage and disposal facilities. Necessary documentation is provided. A minimum of 30 gallons of used 3M specialty fluid is required for participation in this free program.

For additional information on the 3M Used Fluid Return Program, contact your local 3M representative or call 3M Customer Service at 800.810.8513.

Resources

3M™ Novec™ Engineered Fluids are supported by global sales, technical and customer service resources, with technical service laboratories in the U.S., Europe, Japan, Latin America and Southeast Asia. Users benefit from 3M's broad technology base and continuing attention to product development, performance, safety and environmental issues. For additional technical information on 3M™ Novec™ 71DE Engineered Fluid in the United States or for the name of a local authorized distributor, call 3M Electronics Markets Materials Division: **800 810 8513**.

The 3M™ Novec™ Brand Family

The Novec brand is the hallmark for a variety of patented 3M products. Although each has its own unique formula and performance properties, all Novec products are designed in common to address the need for safe, effective, sustainable solutions in industry-specific applications. These include precision and electronics cleaning, heat transfer, fire protection, lubricant deposition and several specialty chemical applications.

3M™ Novec™ Engineered Fluids • 3M™ Novec™ Aerosol Cleaners • 3M™ Novec™ 1230 Fire Protection Fluid • 3M™ Novec™ Electronic Coatings • 3M™ Novec™ Electronic Surfactants

United States	China	Europe	Japan	Korea	Singapore	Taiwan
3M Electronics Markets Materials Division 800 810 8513	3M China Ltd. 86 21 6275 3535	3M Belgium N.V. 32 3 250 7521	Sumitomo 3M Limited 813 3709 8250	3M Korea Limited 82 2 3771 4114	3M Singapore Pte. Ltd. 65 64508888	3M Taiwan Limited 886 2 2704 9011

Product Use: All statements, technical information and recommendations contained in this document are based on tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Warranty and Limited Remedy: Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

Limitation Of Liability: Except where prohibited b.incidental, or consequential regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



Electronics Markets Materials Division

3M Center, Building 224-3N-11
St. Paul, MN 55144-1000
www.3M.com/novec
1-800-810-8513

Please recycle. Printed in USA.
Issued: 12/18 © 3M 2018.
All rights reserved. 7013HB
98-0212-2600-0

3M and Novec are trademarks of 3M Company.
Used under license by 3M subsidiaries and affiliates.